

Fresh Air Hood ZU 10/900



Fresh air hood with fluorescent lighting



Fresh air hood with LED recessed luminaires and video camera (customized solution)

This fresh air hood was particularly designed for the area above the autopsy table. It has a sturdy self-supporting construction and is made of brushed stainless steel (material no. 1.4301 – ANSI 304). The fresh air hood comprises 4 mountings points to mount it to the ceiling by means of threaded bars or steel ropes. Adjustable air fins guarantee even and drought-free airflow and hence prevent the raise of harmful vapors. Glare-free LED recessed luminaires guarantee for very uniform illumination of the illumination area (half-peak divergence: $2 \times 44^\circ$) The fresh air hood is to be connected to a ventilation system provided by the customer.

Technical Data:

Material:	brushed stainless steel (1.4301 – ANSI 304)
Dimensions W/D/H:	1000 x 2400 x 300 mm
Air capacity:	750 m ³ /h
Trajectory range:	approx. 2.0 m
Loss of pressure:	approx. 150 pa
Air-conduction:	adjustable
Lighting:	2 x 76 Watt
Brightness:	approx. 6,000 Lux at a distance of 1.5 m
Luminous flux:	2 x 9,000 lm
Color temperature:	approx. 4,000° Kelvin
Color index:	>80
Half-peak divergence:	2 x 44°
DALI-dimmable as standard	
Service life:	70,000 h
Voltage:	230 Volt / 50 Hz
Exhaust duct diameter:	2 x d= 200 mm
Weight:	approx. 120 kg
Type:	ZU 10/900
Article No.:	010.010.900

TekEquipment™

Ph: 1300 368 138

www.tekequipment.com.au

info@tekequipment.com.au

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0
Fax +49/941/20 86 48-29
www.KUGEL-medical.de

