

Refrigeration unit - Split system



Connector-ready cooling unit, which is ready for immediate use. Mounted directly on top of the morgue. The units have a sturdy housing with low-noise emittance, are fully thermal, and equipped with an air-cooled compressor. The safety utilities are in accordance with EN (DIN) standards, VDE regulations and VBG guidelines. Also included is a high-capacity evaporator with automatic defrosting, an electrical temperature regulation, and a digital temperature indicator with connection and protective plug.

Refrigerant: R 404a

Ambient temperature +5°C up to +45°C

Temperature range: +10°C bis -5°C

Technical data:

Type	Refrigeration Capacity	Voltage	Dimensions	Article No.
SP-KT 100	1013 Watt	230 Volt / 1 Ph / 50 Hz	620 x 719 x 357 mm	040.150.025
SP-KT 130	1194 Watt	230 Volt / 1 Ph / 50 Hz	620 x 719 x 357 mm	040.150.030
SP-KT 180	1699 Watt	230 Volt / 1 Ph / 50 Hz	820 x 809 x 390 mm	040.150.040
SP-KT 220	2108 Watt	400 Volt / 3 Ph / 50 Hz	820 x 809 x 390 mm	040.150.050
SP-KT 320	3747 Watt	400 Volt / 3 Ph / 50 Hz	820 x 929 x 427 mm	040.150.065

Temperatur range: +5°C bis +45°C

Type	Refrigeration Capacity	Voltage	Dimensions	Article No.
SP-TKT 80	868 Watt	230 Volt / 1 Ph / 50 Hz	620 x 719 x 357 mm	040.250.010
SP-TKT 100	1177 Watt	230 Volt / 1 Ph / 50 Hz	820 x 809 x 390 mm	040.250.020
SP-TKT 200	1913 Watt	400 Volt / 3 Ph / 50 Hz	820 x 929 x 427 mm	040.250.030

KUGEL Medizintechnik Vertriebs GmbH Phone +49/9 41/20 86 48-0
Hermann-Köhl-Str. 2A Fax +49/9 41/20 86 48-29
DE – 93049 Regensburg/Germany www.KUGEL-medical.de

TekEquipment™

Ph: 1300 368 138

www.tekequipment.com.au

info@tekequipment.com.au