

Refrigeration unit SP-TKT 200 Freezer - Split system

TekEquipment™

Ph: 1300 368 138

www.tekequipment.com.au

info@tekequipment.com.au



TekMed NZ™

Ph: 0800 456 217

info@tekmed.co.nz

www.tekmed.co.nz

This model consists of a condensing and evaporator unit. The condensing unit has a sturdy housing with low-noise emittance, is fully thermal, and equipped with an air-cooled compressor. The safety utilities are in accordance with EN (DIN) standards, VDE regulations and VBG guidelines. Also included is a high-capacity evaporator with automatic defrosting, electrical temperature regulation and a digital temperature indicator with connection, protective plug and 10 m cable connection to the evaporator. Delivery without copper pipelines.

Refrigerant: R 404a

Ambient temperature +5 °C up to +45 °C

Technical Data:

Temperature range:	-15 °C to -25 °C
Voltage:	400 V / 3 Ph / 50 Hz
Refrigeration capacity 0 °C inside +40 °C outside:	1913 Watt
Rated input (when normally running):	2400 Watt
Rated input:	6,3 Amp
Peak current:	45 Amp
Max current:	12,5 Amp
Defrost:	electric
Defrost heaters:	1400 Watt
Weight Condensing unit:	72 kg
Weight Evaporator:	28 kg
<u>Compressor:</u>	
Type:	Hermetic
Normal power:	1500 Watt
<u>Condenser:</u>	
Air flow:	1500 m ³ /h
<u>Evaporator:</u>	
Air flow:	1800 m ³ /h
Air throw:	4 m (Standard / is affected by many factors)
Dimensions Evaporator W/D/H:	1614 x 410 x 215 mm
Dimensions condensing unit W/D/H:	820 x 427 x 427 mm
Type:	SP-TKT 200
Article No.:	040.250.0

KUGEL Medizintechnik Vertriebs GmbH
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg

Telefon 09 41/20 86 48-0
Telefax 09 41/20 86 48-29
www.KUGEL-medical.de



KUGEL
medical
■ ■ ■ ■