

Working Table for Staining FT-1000 – FT-2500



Working table with formalin sink and sieve (will not be delivered in standard)

TekEquipment™

Ph: 1300 368 138

www.tekequipment.com.au

info@tekequipment.com.au

TekMed NZ™

Ph: 0800 456 217

info@tekmed.co.nz

www.tekmed.co.nz

The working table for staining is equipped with air down draft system. This specialized worktable guarantees a laboratory environment free of pollutants while slicing and preparing histological slide preparations, and is even well suited for small dissections. Airflow travels over the entire working area and is vacuumed out downwards, which provides optimal removal of unsanitary vapours.

MAC (maximum allowable concentration) values for formalin are below target throughout the entire vacuum-effected area. The cutting table is to be connected to a side-mounted exhaust system.

- Entire construction is made of stainless steel (material no. 1.4301 – ANSI 304)
- Stable, self-supporting undercarriage with adjustable legs
- Low overall height of the upper structure increases leg room
- Very stable perforated working plates (approx. 10 mm lower than the circumferential edging), perforation D17, T60
- Air speed onto the perforated surface: min. 0,4m/sec
- Integrated connecting pieces with flow rate regulation
- Integrated sprinkler system below perforated working plates with regulating valve
- Connecting pieces for exhaust air with right or left side option

Technical Data:

Dimensions W/D/H:	1000 x 750 x 750 mm
Exhaust Air capacity:	600 m ³ /h
Material:	Stainless steel (material no. 1.4301 – ANSI 304)
Perforated working area:	approx. 840 x 670 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	200 mm
Type:	FT-1000
Article No.:	060.030.010

Additional models see back page

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0
Fax +49/941/20 86 48-29
www.KUGEL-medical.de



Working Table for Staining FT-1000 – FT-2500

Model FT-1250:

Dimensions W/D/H:	1250 x 750 x 750 mm
Exhaust Air capacity:	800 m ³ /h
Material:	Stainless steel (material no. 1.4301 – ANSI 304)
Perforated working area:	approx. 1090 x 670 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	200 mm
Type:	FT-1250
Article No.:	060.030.015

Model FT-1500:

Dimensions W/D/H:	1500 x 750 x 750 mm
Exhaust Air capacity:	1000 m ³ /h
Material:	Stainless steel (material no. 1.4301 – ANSI 304)
Perforated working area:	approx. 1340 x 670 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	200 mm
Type:	FT-1500
Article No.:	060.030.020

Model FT-1750:

Dimensions W/D/H:	1750 x 750 x 750 mm
Exhaust Air capacity:	1200 m ³ /h
Material:	Stainless steel (material no. 1.4301 – ANSI 304)
Perforated working area:	approx. 1590 x 670 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	FT-1750
Article No.:	060.030.025

Model FT-2000:

Dimensions W/D/H:	2000 x 750 x 750 mm
Exhaust Air capacity:	1400 m ³ /h
Material:	Stainless steel (material no. 1.4301 – ANSI 304)
Perforated working area:	approx. 1840 x 670 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	FT-2000
Article No.:	060.030.030

Modell FT-2250	2250 x 750 x 750 mm	060.030.035
Modell FT-2500	2500 x 750 x 750 mm	060.030.040

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0
Fax +49/941/20 86 48-29
www.KUGEL-medical.de

