

Transport Truck TW 52/500

Hydraulically Height-Adjustable



The Transport truck TW 52/500 has a stable, torsion-resistant frame structure of steel profiles silver-coloured painted, with smooth running, integrated double-hydraulic unit for foot-actuated height-adjustment as well as for length-side tipping. The transport-truck can be lifted or lowered, at the front side and backside (together or separately) 350 mm each, by a special double hydraulic unit. Equipped with 4 steering wheels, 2 of them lockable, 1 direction fixable $d=200$ mm with special ball bearings permanently lubricated and maintenance-free. The very low deadweight permits easy shunting and operation. A stainless steel roller track with 5 carrying rollers on top of the truck, as well as a holding device for a body tray, or a washing table plate WTP 10/600. At the front-side a slide handle.

Technical Data:

Dimensions lowest Position W/D/H:	2150 x 650 x 530 mm
Dimensions highest Position W/D/H:	2150 x 650 x 900 mm
Carrying capacity:	max. 200 kg
Dead weight:	ca. 80 kg
Material:	Steel
Colour:	silver painted
Type:	TW 52/500
Article No.:	050.150.050

TekEquipment™

Ph: 1300 368 138

www.tekequipment.com.au

info@tekequipment.com.au

TekMed NZ™

Ph: 0800 456 217

info@tekmed.co.nz

www.tekmed.co.nz

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0
Fax +49/941/20 86 48-29
www.KUGEL-medical.de



KUGEL
medical