Down-Draft Grossing Table UCS-E-2000-B with bridge and integrated Illumination

Table with accessories (will not be delivered in standard)

The down-draft grossing table is equipped with air down draft system. This specialized work table guarantees a laboratory environment free of pollutants while slicing and preparing histological slide preparations and is even well suited for small dissections. Airflow travels over the entire working area and is vacuumed out downwards, which provides optimal removal of unsanitary vapours. MAC (maximum allowable concentration) values for formalin are below target throughout the entire vacuum-effected area. The cutting table is to be connected to an exhaust system provided by the customer.
The UCS-E-2000-B model includes the following features:

- Workstations with a large surface area
- Entire construction is made of stainless steel (Material no. 1.4301 – ANSI 304)
- Stable, self-supporting undercarriage with adjustable legs
- Low overall height of the upper structure increases leg room
- Height adjustable from 750 to 1000 mm
- Height adjustable with UP/Down push bottom
- Work surface includes a seamlessly welded basin measuring 400 x 400 x 200 mm
- Basin includes integrated air vacuum
- Very sturdy, perforated and insertable working plates
- Integrated sprinkler system with adjustable valve for bath sanitation located underneath the perforated working plates
- Formalin sink with sieve insert
- Mixing tap with detachable cold and hot water shower
- Exhaust duct
- Build in Illumination with “Daylight” Quality approx. 5000°K for direct photograph without additional Flashlights
- 2x 230 Volt Electric socket outlet

Technical data see back page

KUGEL Medizintechnik Vertriebs GmbH
Hermann-Köhl-Str. 2A
DE – 93049 Regensburg / Germany

Phone +49/941/208648-0
Fax +49/941/208648-29
www.KUGEL-medical.de

zertifiziert nach ISO 9001

TekEquipment™
Ph: 1300 368 138
www.tekequipment.com.au
info@tekequipment.com.au

Down-Draft Grossing Table UCS-E-2000-B with bridge and integrated Illumination

Technical Data:

Dimensions Table W/D/H:	2100 x 1000 x 2000 mm
Dimensions Illumination:	2100 x 600 mm
Height adjustable:	from 750 to 1000 mm
Exhaust Air capacity:	1600 m³/h
Material:	Stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1540 x 920 mm
Cold / Warm water connection:	½”
Waste water connection:	2”
Exhaust duct diameter:	250 mm
Type:	UCS-E-2000-B
Article No.:	060.020.040

Accessories:

Waste bin on the UCS
Art.-No. 060.012.056

Magnifier with illumination
Art.-No. 060.015.050

Kameraholder on the railingsystem KA-05
Art.-No. 060.015.081

Dictaphone holder Art.-No. 060.020.041
Document holder Art.-No. 060.012.031
Formalin dispensing system Art.-No. 060.012.024

Cutting board "CORIAN"
with ruler Art.-No. 060.019.030

KUGEL Medizintechnik Vertriebs GmbH
Hermann-Köhl-Str. 2A
DE – 93049 Regensburg / Germany

Phone +49/941/208648-0
Fax +49/941/208648-29
www.KUGEL-medical.de

zertifiziert nach ISO 9001

TekEquipment™
Ph: 1300 368 138
www.tekequipment.com.au
info@tekequipment.com.au

Down-Draft Grossing Table UCS
Dual Working Place

TekEquipment™
Ph: 1300 368 138
www.tekequipment.com.au
info@tekequipment.com.au

TekMed NZ™
Ph: 0800 456 217
info@tekmed.co.nz
www.tekmed.co.nz

The down-draft grossing table is equipped with air down draft system. This specialized work table guarantees a laboratory environment free of pollutants while slicing and preparing histological slide preparations and is even well suited for small dissections. Airflow travels over the entire working area and is vacuumed out underneath, which provides optimal removal of unsanitary vapours.
MAC (maximum allowable concentration) values for formalin are below target throughout the entire Vacuum-effected area. The cutting table is to be connected to a side-mounted exhaust system - provided by the customer.
The UCS models include the following features:

- Dual working place
- Workstations with a large surface area
- Entire construction is made of stainless steel
- Stable, self-supporting undercarriage with adjustable legs
- Low overall height of the upper structure increases leg room
- Work surface includes a seamlessly welded basin measuring 400 x 400 x 200 mm
- Basin includes integrated air vacuum
- Basin can be mounted to the right or left side
- Very sturdy, perforated and insertable working plates
- Integrated sprinkler system with adjustable valve for bath sanitation located underneath the perforated working plates
- Formalin sink with sieve insert
- Mixing tap with detachable cold and hot water shower
- Exhaust duct left or right side

Technical Data:

Dimensions W/D/H:	1500 x 1000 x 750 mm
Exhaust Air capacity:	1000 m^3/h
Material:	Stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 960 x 920 mm
Cold / Warm water connection:	½”
Waste water connection:	2”
Exhaust duct diameter:	250 mm
Type:	UCS-1500-D
Article No:	060.010.015

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE – 93049 Regensburg / Germany

Phone +49/941/208648-0
Fax +49/941/208648-29
www.KUGEL-medical.de

zertifiziert nach ISO 9001

KUGEL medical

Down-Draft Grossing Table UCS
Dual Working Place

Model UCS-1750-D:

Dimensions W/D/H:	1750 x 1000 x 750 mm
Exhaust Air capacity:	1300 m³/h
Material:	Stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1210 x 920 mm
Cold / Warm water connection:	½”
Waste water connection:	2”
Exhaust duct diameter:	250 mm
Type:	UCS-1750-D
Article No:	060.010.025

Model UCS-2000-D:

Dimensions W/D/H:	2000 x 1000 x 750 mm
Exhaust Air capacity:	1600 m³/h
Material:	Stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1460 x 920 mm
Cold / Warm water connection:	½”
Waste water connection:	2”
Exhaust duct diameter:	250 mm
Type:	UCS-2000-D
Article No:	060.010.035

Model UCS-2250-D:

Dimensions W/D/H:	2250 x 1000 x 750 mm
Exhaust Air capacity:	1900 m³/h
Material:	Stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1700 x 920 mm
Cold / Warm water connection:	½”
Waste water connection:	2”
Exhaust duct diameter:	250 mm
Type:	UCS-2250-D
Article No:	060.010.038

Model UCS-2500-D:

Dimensions W/D/H:	2500 x 1000 x 750 mm
Exhaust Air capacity:	2200 m³/h
Material:	Stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1960 x 920 mm
Cold / Warm water connection:	½”
Waste water connection:	2”
Exhaust duct diameter:	250 mm
Type:	UCS-2500-D
Article No:	060.010.045

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE – 93049 Regensburg / Germany

Phone +49/941/208648-0
Fax +49/941/208648-29
www.KUGEL-medical.de

zertifiziert nach ISO 9001

KUGEL medical

Subject to technical modifications as required by products improvements (Version 01/2014)

Down-Draft Grossing Table UCS
Electrically Height-Adjustable

TekEquipment™
Ph: 1300 368 138
www.tekequipment.com.au
info@tekequipment.com.au

TekMed NZ™
Ph: 0800 456 217
info@tekmed.co.nz
www.tekmed.co.nz

The down-draft grossing table is equipped with air down draft system. This specialized work table guarantees a laboratory environment free of pollutants while slicing and preparing histological slide preparations and is even well suited for small dissections. Airflow travels throughout the entire working area and is vacuumed out downwards, which provides optimal removal of unsanitary vapours. MAC (maximum allowable concentration) values for formalin are below target throughout the entire vacuum-effected area. The cutting table is to be connected to a side-mounted exhaust system provided by the customer.

The UCS-E-1500-D model includes the following features:

- Dual working place
- Workstations with a large surface area
- Height-adjustable from 750 to 1000 mm
- Sturdy, self-supporting undercarriage with adjustable legs
- Low overall height of the upper structure increases leg room
- Work surface includes a seamlessly welded basin measuring 400 x 400 x 200 mm
- Basin includes integrated air vacuum
- Basin can be mounted to the right or left side
- Very sturdy, perforated and insertable working plates
- Integrated sprinkler system with adjustable valve for bath sanitation located underneath the perforated working plates
- Formalin sink with sieve insert
- Mixing tap with detachable cold and hot water shower
- Exhaust duct left or right side

Technical Data:

Dimensions W/D/H:	1500 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	Min. 1000 m^3/h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 960 x 920 mm
Cold / Warm water connection:	½”
Waste water connection:	2”
Exhaust duct diameter:	250 mm
Type:	UCS-E-1500-D
Article No:	060.100.015

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE – 93049 Regensburg / Germany

Phone +49/941/208648-0
Fax +49/941/208648-29
www.KUGEL-medical.de

zertifiziert nach ISO 9001

KUGEL medical

Down-Draft Grossing Table UCS
Electrically Height-Adjustable

Model UCS-E-1750-D:

Dimensions W/D/H:	1750 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	1300 m³/h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1210 x 920 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	UCS-E-1750-D
Article No:	060.100.025

Model UCS-E-2000-D:

Dimensions W/D/H:	2000 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	1600 m³/h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1460 x 920 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	UCS-E-2000-D
Article No:	060.100.035

Model UCS-E-2250-D:

Dimensions W/D/H:	2250 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	1900 m³/h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1700 x 920 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	UCS-E-2250-D
Article No:	060.100.050

Model UCS-E-2500-D:

Dimensions W/D/H:	2500 x 1000 x 750 / 1000 mm
Exhaust Air capacity:	2200 m³/h
Material:	Brushed stainless steel (Material No. 1.4301 – ANSI 304)
Perforated working area:	approx. 1960 x 920 mm
Cold / Warm water connection:	½"
Waste water connection:	2"
Exhaust duct diameter:	250 mm
Type:	UCS-E-2500-D
Article No:	060.100.055

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE – 93049 Regensburg / Germany

Phone +49/941/208648-0
Fax +49/941/208648-29
www.KUGEL-medical.de

zertifiziert nach ISO 9001

KUGEL medical

Subject to technical modifications as required by products improvements (Version 01/2014)